



NOTES:
 HOUSING: HIGH TEMPERATURE HOUSING UL94V-0
 WITHSTANDS IR AND VPR SOLDERING METHODS.
 CONTACTS: PHOSPHOR BRONZE.
 PLATING: GOLD PLATED.
 ELECTRICAL CHARACTERISTICS:
 CURRENT RATING:0.3 AMP.
 INSULATOR RESISTANCE:1000MΩ MIN. AT DC 250V.
 CONTACT RESISTANCE: 90MΩ MAX. AT DC 100MA.
 OPERATING TEMPERATURE:-55°C ~+85°C .

60	13.10	12.30	11.60	9.60
50	11.10	10.30	9.60	7.60
40	9.10	8.30	7.60	5.60
34	7.90	7.10	6.40	4.40
30	7.10	6.30	5.60	3.60
24	5.90	5.10	4.40	2.40
20	5.10	4.30	3.60	1.60
Pin No.	DIM A	DIM B	DIM C	DIM D

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW
			CHANGE.
			CHECK.
			APPRO.

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	0.4mm BTB H1.5mm	
CHECKED			PART NO. GP02-8XX-GXXP-BOR	
APPROVALS			SCALE: 1:1	
TOLERANCES ARE		ANGLE	UNIT: mm	PROJ.
30~以上	±0.30			
10~30	±0.20	±2°	DRAWING NO.	
5~10	±0.15			
~ 5	±0.10			



深圳市联丰电子有限公司
 SHENZHEN LINFENG ELECTRONIC CO.,LTD