



PCB Layout Diagram

Top View

**NOTE:**

**1. MATERIAL:**

- a. HOUSING: PA66
- b. CONTACT: PHOSPHOR BRONZE
- (SURFACE PLATING: Ni 100u")

SEE ORDERING INFORMATION

**2. ELECTRIC:**

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.25MM	Ni-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.25MM	Ni-Plating
1	HOUSING	1	PA66	BLACK
NO	PART NAME	QTY	MATERIAL	PLATING & COLOR

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

<b>APPROVALS</b>		<b>DATE</b>	<p><b>深圳市联丰电子有限公司</b> SHENZHEN LINFENG ELECTRONIC CO.,LTD</p>	<b>TITLE:</b>	电池座
<b>DRAWN</b>	ZHIWEI.CHEN	2015.07.07		<b>PART NO.</b>	GP07-CR2032-10
<b>CHECKED</b>				<b>UNIT:</b> mm	<b>SCALE:</b> 1:1
<b>APPROVALS</b>			<b>TOLERANCES ARE</b>	<b>PROJ:</b>	
			30~以上 ±0.30	<b>DRAWING NO.</b>	
			10~30 ±0.20		
			5~10 ±0.15		
			~ 5 ±0.10	<b>ANGLE</b>	±2°
				<b>SHEET</b>	1 OF 1