



PCB Layout Diagram
Top View

NOTE:
 1.MATERIAL:
 a.HOUSING:PA66 UL94V-0
 b.CONTACT:BRASS
 (SURFACE PLATING: Ni100u"-120u")
 SEE ORDERING INFORMATION
 2.ELECTRIC:
 a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
 b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 d.OPERATING TEMPERATURE: -25° C ~ +85° C

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:			
DRAWN	ZHIWEI.CHEN	2015.07.07	*****			
CHECKED			PART NO. GP07-CR2032-18			
APPROVALS			UNIT: mm SCALE: 1:1 PROJ:			
TOLERANCES ARE		30~ ^{以上}	±0.30	ANGLE	±2'	DRAWING NO.
		10~30	±0.20			
		5~10	±0.15			
		~ 5	±0.10			
DRAWN			SHENZHEN LINENYING ELECTRONIC CO.,LTD			
DATE			深圳市联丰电子有限公司			
DRAWING NO.			GP07-CR2032-18			
SCALE			1:1			
SHEET			1 OF 1			