



NOTE:

1.MATERIAL:

- a.HOUSING:PBT BLACK
- b.CONTACT:PHOSPHOR BRONZE
- (SURFACE PLATING: Ni100U~120U")

SEE ORDERING INFORMATION

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -25° C ~ +85° C

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	<p>深圳市联丰电子有限公司 SHENZHEN LINFENG ELECTRONIC CO.,LTD</p>			
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	*****		
CHECKED			PART NO.	GP07-CR1220-02		
APPROVALS			UNIT: mm	SCALE: 1:1	PROJ:	
TOLERANCES ARE		30~ø1.5 ±0.30	ANGLE	±2°	DRAWING NO.	
		10~30 ±0.20				
		5~10 ±0.15				
		~ 5 ±0.10				
SHEET 1 OF 1						