



PCB Layout Diagram

Top View

NOTE:

1. MATERIAL:

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: PHOSPHOR BRONZE (SURFACE PLATING: A*u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.20MM	Gold Plating and Ni Under-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.20MM	Gold Plating and Ni Under-Plating
1	HOUSING	1	PPS	BROWN
	PART NAME	Q' TV	MATERIAL	PLATING & COLOR
	NO.			
	ECN NO.	REV.	DATE.	DESCRIPTION.
	A			NEW
				CHANGE.
				CHECK.
				APPRO.

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	电池座 PPS SMT	
CHECKED			PART NO. GP07-CR1220-01	
APPROVALS			SCALE: 1:1	PROJ:
TOLERANCES ARE		ANGLE	UNIT: mm	SHEET 1 OF 1
30 [±] 0.30	±0.30	±2°	DRAWING NO.	
10 [±] 0.20	±0.20			
5 [±] 0.15	±0.15			
~ 5	±0.10			

深圳市联丰电子有限公司
SHENZHEN LINFENG ELECTRONIC CO., LTD